CAR ROCKER COMBO

Instructions

Maintenance:

- Before each use, make sure all the fasteners are firmly tightened and all the parts are securely fastened.
- Always wipe the product with a plane, dry cloth regularly and avoid using harsh chemicals.

- The product must be assembled by an adult only. Keep all the parts out of the reach of kids until the product is fully assembled.
- For safety, kids should always face forward while riding the car rocker.
- Packaging materials are not safe to play with and should be kept away from kids.
- Always use the product on an even surface. Using it on a rough surface can make it unsteady and may cause injuries.
- Adult supervision is recommended when kids are using this product.

- Always assemble on a non-abrasive surface to avoid scratches and make sure there are no sharp objects placed nearby.
- Avoid over-tightening the nuts as it may cause damage to the parts.

Warning: Before using as a car ride on, make sure no nut is fixed between the rear wheels.

Part Details



Car Body Assembly x 1 (with a pre-fitted nut between rear wheels)



Front Wheel Assembly x 1 (with a pre-fitted nut)



Steering x 1



Instruction Manual x 1

List of Parts	No.
Car Body Assembly	1
Front Wheel Assembly	1
Rocker Base	1
Steering	1
Instruction Manual	1



Rocker Base x 1

Assembly

Instructions



Car Body Assembly x 1



Front Wheel Assembly x 1

Required Assembly Parts



Steering x 1

Before starting the assembly, lay out a carpet on the floor to avoid scratches.







- A. Take the front wheel assembly and remove the pre-fitted nut.
- Remove the pre-fitted nut between the rear wheels of the car body assembly.
- Insert the axle of the front wheel assembly through the base hole of the car body and push it until it protrudes from the top hole as shown in the image.





Take the steering and put it on the top of front wheel axle (horn should be oriented towards the front) and fasten both together with the front assembly nut that you removed earlier.

Note: 1. Avoid overtightening the nut as it may cause damage to the components. Tighten just enough to ensure a secure fit without applying excessive force. If you notice any restriction in movement of the steering after tightening, loosen the nut slightly.

2. Before using as a car ride on, make sure no nut is fixed between the rear



Before starting the assembly, please ensure that the part quantity matches the numbers listed in the manual. If you find any discrepancies in the part count or encounter any product-related issues, feel free to reach out to us at +918221001033 or connect with us via WhatsApp in between 9:30-6PM, Monday to Saturday. We're here to assist you!



Scan to Connect

DISCLAIMER: ACTUAL PRODUCT COLOR MAY VARY FROM THAT SHOWN IN THE IMAGE







Align the locking tab between the front wheels of the car ride on (subassembly- step 1) with the rounded square hole on the rocker base and firmly push the subassembly downwards until the locking tab is engaged with the rocker base.



Press down on the rear portion of the car ride on subassembly making sure the threaded pin (between the rear wheels) passes through the rounded rectangular hole on the rocker base. Put the car body nut (removed in step 1) onto the protruding end of the threaded pin and tighten.

Your versatile Car Rocker Combo, designed to function both as a Ride On and a Rocker, is now ready for use!



Warning: Before using as a car ride on, make sure no nut is fixed between the rear wheels.